

加热线缆 Heating Wire Cable

铁氟龙绝缘碳纤维加热线 Teflon Insulation Carbon Fiber Heating Wire

技术资料:

产品标准: GJB773A/8A - 2000
额定电压: 600V
工频耐压: 3500V
温度范围: -60°C~+200°C
导体: 日本原装碳丝、T700SC
电阻范围: 450 133 66 33 17Ω / m
碳纤规格: 1K 3K 6K 12K 24K
绝缘体: 单层或双层铁氟龙

Technical data:

Product Standard: GJB773A/8A - 2000
Rated Voltage: 600V
power-frequency withstand voltage: 3500V
Temperature Range: -60°C~+200°C
Conductor: the original Japanese Carbon filament、T700SC
Resistance: 450 133 66 33 17Ω / m
Carbon Fiber Specification: 1K 3K 6K 12K 24K
Insulation: Single or double layer Teflon

适用领域:

碳纤维红外电热线是一种节能型电热体, 采用进口高级碳纤维为发热体具有很高的机械强度和极长的使用寿命, 电热线重量轻, 柔软, 可弯成各种形状, 易制成多种电热元件组合模块, 能方便得适用各种加热场合的需求。

产品广泛应用于: 暖风机、取暖器、空调器、浴霸; 汽车烤漆房; 食品、木材、家具、烟草等烘干或干燥机械; 光波房等远红外保健食品; 农业大棚种植保温; 食品, 面包等烘烤机。

Application Field:

Carbon fiber infrared electric heating wire is a type of Energy saving electric heater,

Use imported carbon fiber as heating body, has very high mechanical strength and very long use service life, Light weight, soft, can be bent into a variety of shapes, Easy to make a variety of electric heating element combination module and can be convenient to apply to the needs of various heating occasions.

Products are widely used in heaters, heaters, air conditioners, bath heater, automobile paint baking room, food, wood, furniture, tobacco and other drying or drying machine.

产品示意图 Product Schematic Diagram:



加热线缆 Heating Wire Cable

硅胶碳纤维发热线 Silicone Rubber Carbon Fiber Heating Wire

技术资料:

额定电压: 300V

温度范围: 200°C

导体: 碳纤维

绝缘体: 硅橡胶

外径公差: $\pm 0.15\text{mm}$

颜色: 黑-棕-红-橙-黄-绿-蓝-紫-灰-白-黄/绿等

线径范围: $\Phi 1.5 - 5.0\text{mm}$

电阻范围: 450 133 66 33 17 Ω / m

碳纤规格: 1K 3K 6K 12K 24K

特性: 耐高温、低温、碱、耐燃烧、老化, 耐候性、防霉以及优良的柔软性、电绝缘性、满足UL、ROHS的要求, 具备远红外功能。

Technical data:

Rated Voltage: 300V

Temperature Range: 200°C

Conductor: Carbon Fiber

Insulation: Silicone rubber

O.D. Tolerance: $\pm 0.15\text{mm}$

Colour: Black-Brown-Red-Orange-Yellow-Green-Blue-Purple-Gray-White-Yellow/Green Line

Line Diameter Range: $\phi 1.5 - 5.0\text{mm}$

Resistance: 450 133 66 33 17 Ω / m

Carbon Fiber Specification: 1K 3K 6K 12K 24K

Properties: High and low temperature resistant, alkali-resisting, flame resistant, anti-aging, weather ability, mildew proof and good flexibility, electrical insulation, and meet with UL、ROHS requirement, have far infrared function.

产品示意图 Product Schematic Diagram:



适用领域:

适用范围: 电热毯, 玉石床垫, 玉石坐垫, 理疗床, 瘦身腰带, 医疗器械, 美容器材等行业。

Application Field:

Apply to electric blanket, jade cushion, physical therapy bed, slimming belt, medical and beauty equipment, etc.